Technisches Datenblatt

Technical data sheet

Starke Verbindung
Kluge Technik
Strong contacts
Clever technology



Übergangsprofil Nr. 132, 38 mm

- Aluminium.
- Selbstklebend.

TÜV Zertifikat-Nr. 44 780 14206215

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)
Pulverbeschichtung:	optional (RAL/Metallic/Holzdekor)

Klebstoff
Schmelzhaftklebstoff (synthetische Kautschukbasis)
Viskosität: 10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)
FDA Status: gemäß § 175.105 Adhesives
Transportschutz: abgedeckt mit Silikonpapier

Geeignet für: Laminat / Multilayer
Montageart: Kleben
Längen: 300 cm, 270 cm, 100 cm, 90 cm
Farben: gold, sahara, silber, bronze, Edelstahl matt, Edelstahl gebürstet, schwarz pulverbeschichtet (RAL 9005), anthrazit metallic, grau metallic, bronze metallic, Buche, Eiche dunkel, Eiche hell, Ahorn, Nussbaum, Eiche hellgrau, Eiche grau

Übergangsprofile schaffen Übergänge zwischen nahezu beliebigen, gleichhohen Bodenbelägen.
Die in verschiedensten Breiten, Formen, Materialien und Farben erhältlichen Profile lassen sich schnell und unkompliziert verlegen.

Connection section no. 132, 38 mm

- Aluminium.
- Auto-adhesive.

TÜV certification no. 44 780 14206215

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)
Powdercoating:	optional (RAL/metallic/woodstyle)

Adhesive
hotmelt adhesive (synthetic rubber-based)
Viscosity: 10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)
FDA state: acc. to § 175.105 Adhesives
Protection: covered with silicone paper

Suitable for: Laminate / multilayer
Installation: gluing
Lengths: 300 cm, 270 cm, 100 cm, 90 cm
Colours: gold, sahara, silver, bronze, stainless steel matt, stainless steel brushed, black powdercoated (RAL 9005), anthracite metallic, grey metallic, bronze metallic, beech, oak dark, oak light, maple, walnut, Oak light grey, Oak grey

Connection sections create transitions between almost any level of flooring.
The profiles are available in a wide range of shapes, materials and colors and can be laid quickly and easily.

Carl Prinz GmbH & Co. KG
von-Monschaw-Str. 5, D-47574 Goch
www.carlprinz.de

Mit Erscheinen dieses Dokuments verlieren alle Vorgängerversionen ihre Gültigkeit.
With publication of this document all former versions are invalid.